



6304 Bearing 2D drawings and 3D CAD models

FAG 6304 2RSR C3 Single Row Radial Bearing
(SKF 2RS, Timken 304PP, NTN VV NSK)

Bearing No. 6304

Size	52x20x15 mm
Bore Diameter	52 mm
Outer Diameter	20 mm
Width	15 mm
d	20 mm
D	52 mm
B	15 mm
d ₁	30.35 mm
D ₂	44.71 mm
r _{1,2} - min.	1.1 mm
d _a - min.	27 mm
D _a - max.	45 mm
r _a - max.	1 mm
Basic dynamic load rating - C	16.8 kN
Basic static load rating - C ₀	7.8 kN
Fatigue load limit - P _u	0.335 kN
Reference speed	30000 r/min
Limiting speed	19000 r/min
Calculation factor - k _r	0.03
Calculation factor - f ₀	12
Category	Single Row Ball Bearings
Inventory	95.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



Super&Victory Industrial & Machinery ...

Weight / Kilogram	0.146
EAN	7316571124742
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	6304
Weight / LBS	0.32
Bore	0.787 Inch 20 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
d ₁	30.35 mm
D ₂	44.71 mm
d _a min.	27 mm



Super&Victory Industrial & Machinery ...

D_a max.	45 mm
r_a max.	1 mm
Basic dynamic load rating C	16.8 kN
Basic static load rating C_0	7.8 kN
Fatigue load limit P_u	0.335 kN
Calculation factor k_r	0.03
Calculation factor f_0	12
Mass bearing	0.14 kg